

## VTS Range Silent Oil Free Air Compressors



Model	L/Min	Ltrs	Bar	Kw / HP	Volts / Hz	dB (A)	CM h x w x d	Surgeries
VTS75	120	23	8	0.55 / 0.75	220-240 / 50	54	64 x 90 x 41	1
VTS75 D	120	23	8	0.55 / 0.75	220-240 / 50	54	64 x 90 x 41	1
VTS150	175	23	8	1.1 / 1.5	220-240 / 50	54	64 x 90 x 41	2
VTS150D	175	23	8	1.1 / 1.5	220-240 / 50	54	64 x 90 x 41	2
VTS200	220	23	8	1.5 / 2.0	220-240 / 50	54	64 x 90 x 41	3
VTS200D	220	23	8	1.5 / 2.0	220-240 / 50	54	64 x 90 x 41	3

FAD L/Min	1 Bar	2 Bar	3 Bar	4 Bar	5 Bar	6 Bar	7 Bar	8 Bar
VTS75	108	96	85	74	65	57	48	45
VTS75D	108	96	85	74	65	57	48	45
VTS150	159	153	142	130	119	110	99	96
VTS150D	159	153	142	130	119	110	99	96
VTS200	193	178	164	150	142	130	122	116
VTS200D	193	178	164	150	142	130	122	116

D denotes compressor with integral air dryer -40°C Dewpoint  
 Allow +30cm all around compressor for adequate cooling